

# CHIEFTAIN 2100X BIVITEC

The Powerscreen® Chieftain 2100X is available with a 2 deck version of the Binder+Co BIVITEC screen for applications where the feed contains damp, fibrous or matted materials that clog the screen openings of conventional machines. The Chieftain 2100X BIVITEC has 3 movements taking place providing the powerful screening actions required for these difficult materials. The entire screenbox moves in the same circular motion as other Powerscreen® incline screens whilst each of the 2 individual screens resonate causing the flexible polyurethane screen mats to continually tension and un-tension. This powerful screening action eliminates ‘blinding’ and makes screening effective in all weather conditions.

**Features & Benefits**

- Powerful screening action keeps the screen openings clear
- Suitable for screening damp, fibrous or matted materials
- Suitable for sizing materials ranging between 0.5mm–80mm
- Vibration parameters are individually adjustable for each screening deck
- Single drive screen mechanism, low energy consumption
- Quick to change screen mats
- Screen walkway and access ladder
- Hydraulic folding conveyors with excellent stockpiling capacity

**Options**

- Radio controlled tracking
- Roll-in bogie prepared
- Roll-in bogie equipped
- Dual Power (additional electric hydraulic drive)
- Dust suppression
- Auto lubrication system
- Vibrating grizzly
- Anti roll-back



CHIEFTAIN 2100X BIVITEC	TRACK
Weight (Est)	35,500kg (78,264 lbs)
Transport width	3m (9'10")
Transport length	18.23m (59'10")
Transport height	3.47m (11'5")
Working width	18.3m (60')
Working length	19.47m (63'11")
Working height	6.29m (20'8")

\*Output potential depends on application  
Engines are available that are certified to US EPA and EU off road diesel emission standards. Talk to your dealer about possible certification options (i.e. Tier 3 / Stage IIIA, Tier 4 / Stage IIIB, Tier 4 / Stage IV).

