

H5163R

The Powerscreen® H range features horizontal screens ideal for handling high volumes of sticky materials and for the exact, fine sizing demanded in many construction contracts.

The adjustable elliptical throw combines linear and circular amplitude producing an aggressive screening action. Powerscreen® H products are especially effective for scalping after a primary impact or jaw crusher and really have outstanding performance when screening out specific small sizes. Ideally suited to applications such as natural and crushed aggregate, coal, iron ore, recycled concrete and asphalt.

Features & Benefits

- High capacity variable speed belt feeder
- Oil bath screenbox bearing lubrication
- Screen walkway and access ladder
- Hydraulic folding stockpiling conveyors
- Heavy duty triple shaft screenbox with adjustable stroke, angle and speed
- Elliptical throw adjustable up to 19mm (3/4")
- Diesel hydraulic power unit
- Heavy duty, low ground pressure tracks
- Direct feed hopper with impact bars and rollers
- Mid-over's product tail conveyor
- Oversize product side conveyor

Options

- Radio controlled tracking
- Roll-in bogie prepared
- Roll-in bogie equipped
- Variable speed incline apron feeder
- Chute arrangements offering blending between decks



H5163R

Weight (Est)	35,000kg (77,161lbs)
Transport width	3.1m (10'2")
Transport length	17.87 (58'7")
Transport height	3.4m (11'2")
Working width	16.32m (53'7")
Working length	18.6m (61')
Working height	4.63m (15'2")

*Output potential depends on application
Engines are available that are certified to US EPA and EU off road diesel emission standards. Talk to your dealer about possible certification options (i.e. Tier 3 / Stage IIIA, Tier 4 / Stage IIIB, Tier 4 / Stage IV).

