



A TEREX BRAND



COMPACT CRUSHING & SCREENING EQUIPMENT

COMPACT | EASY TO OPERATE | OPTIMAL MATERIAL FLOW



EvoQuip offers a comprehensive range of crushing and screening products to suit a wide variety of industries. The EvoQuip range starts with the Bison 35 crusher capable of outputting up to 30 tph / 34 US tph and goes up to the Cobra 290 crusher capable of outputting 290 tph / 320 US tph.



BUILDING & CONSTRUCTION

EvoQuip machines are easy to transport and can come directly to your site to crush and screen the waste from your demolition projects. Onsite recycling allows you to turn your existing waste into reusable and sellable products increasing your profits and reducing your carbon footprint.



LANDSCAPING

Due to the very compact dimensions of EvoQuip equipment it can overcome access issues due to narrow lanes and country roads. The equipment can come directly to your home to screen top soil for home gardens or golf courses; crush material from worn driveways and brick walls.



PLANT & TOOL HIRE

EvoQuip machines can be used in small to medium sized quarries to process natural material into sellable products. With optional add ons it is possible to produce a variety of aggregates in a single step.



FARMING & AGRICULTURE

EvoQuip equipment can offer agricultural contractors an opportunity to diversify in the off season, helping to retain staff and ensure a steady workload throughout the year. When you are not farming use EvoQuip equipment to demolish old farm buildings, process material for lanes, driveways and drainage stones. Certain models in the range can be transported on an agricultural trailer.



QUARRIES

The versatility and compact nature of the EvoQuip range creates a natural addition for plant & tool hire companies. With the ease of use and weights ranging from 3.2 tonnes to 28 tonnes, the EvoQuip machines are suitable for rental into everything from light residential to heavy commercial use.

GRUSHERS



CRUSHING RANGE

BISON 35



HOPPER / FEEDER

Belt Feeder as standard
Variable speed

JAW CRUSHER

480mm x 250mm (19" x 10") Jaw Inlet
CSS Range: 15mm to 80mm (5/8" to 3-1/4")
Hydraulic Jaw adjustment

POWERUNIT

Tier 3: 21kW / 28.5Hp Isuzu Engine
Direct drive

OUTPUT POTENTIAL

Up to 30tph / 34 US tph

CONVEYORS

400mm (16") wide product conveyor
Product conveyor discharge height: 1100mm (3'4")

GENERAL

Available in both rubber tracked and wheeled versions
Remote control as standard

TRANSPORT

Containerisable
Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	4.45m (14'7")	1.5m (4'11")	2.05m (6'9")
Wheeled Unit	5.25m (17'2")	1.45m (4'9")	2.2m (7'3")

Weight: 3,400Kgs (7,496lbs)

CRUSHING RANGE

BISON 120



HOPPER / FEEDER

2.3m³ (3yd³) Hopper capacity
Grizzly feeder as standard
30mm (1-1/4") Nominal spacing grizzly

JAW CRUSHER

680mm x 400mm (27" x 16") Jaw Inlet
CSS Range: 20mm to 80mm (3/4" to 3-1/4")
Hydraulic Jaw adjustment

POWERUNIT

Tier 3: 61kW/ 83Hp engine
Tier 4: Final: Stage IIIB 52kW/70Hp Isuzu engine
Hydraulic drive crusher

OUTPUT POTENTIAL

Up to 80tph / 90 US tph

CONVEYORS

800mm (32") Wide product conveyor
Product conveyor discharge height: 1.9m (6'2")
Hydraulic folding as standard for transport

GENERAL

Jaw level sensor as standard and remote control as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	5.58m (18' 4")	2.28m (7'6")	2.74m (9')

Weight: 12,000Kgs (26,455lbs)

CRUSHING RANGE

BISON 280

HOPPER / FEEDER

3.6m³ (4.7yd³) Hopper capacity
Two stage grizzly feeder as standard
50mm (2") Nominal spacing grizzly

JAW CRUSHER

900mm x 600mm (36"x24") Jaw inlet
Min CSS: 40mm (1.5") Recycle / 50mm (2") in natural rock
Max CSS: 130mm (5")
Hydraulic jaw adjustment

POWERUNIT

Stage IIIA Constant Speed: John Deere 4045 126 kw (169hp)
Tier 4 Final: Caterpillar C4.4 129kW (173Hp)
Stage V: Caterpillar C4.4 129 kW (173hp)
Direct drive to crusher via clutch and V belts

OUTPUT POTENTIAL

Up to 200 tph / 220 US tph

CONVEYORS

800mm (32") Wide product conveyor
Product conveyor discharge height: 2.9m (9'6")

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	12.4m (40'8")	2.4m (7'10")	3.2m (10'6")

Weight Tier 3: 27,700Kgs (61,068lbs)
Tier 4F: 27,500Kgs (60,627lbs)
*including dirt conveyor and magnet



CRUSHING RANGE

COBRA 230



HOPPER / FEEDER

2.6m³ (3.4yd³) Hopper Capacity
 Integrated pre-screen for fines removal
 Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

860mm (34") x 720mm (28.5") Crusher Inlet
 830mm (33") Wide x 860mm (34") diameter rotor
 2 High / 2 Low configuration as standard
 Max OSS – 120mm (4.75") upper; 55mm (2.25") lower
 Min CSS – 40mm (1.5") upper; 20mm (0.75") lower
 Hydraulic adjust and hydraulic overload protection as standard

POWERUNIT

Stage IIIA Constant Speed: John Deere 6068 194 kw (260hp)
 Tier 4 Final: Volvo D8 210kW (281Hp)
 Stage V: Volvo D8 210kW (281Hp)
 Direct Drive to Crusher via clutch and V Belts

OUTPUT POTENTIAL

Up to 250tph / 275 US tph

CONVEYORS

900mm (36") wide product conveyor
 Product conveyor discharge height: 3000mm (9' 10")

GENERAL

Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.32m (30' 7")	2.43m (8')	2.99m (9' 10")

Weight (with Magnet) Tier 3: 23,700Kgs (52,250lbs)
 Tier 4F: 24,000Kgs (52,911lbs)

CRUSHING RANGE

COBRA 230R

HOPPER / FEEDER

2.6m³ (3.4yd³) Hopper Capacity
 Integrated pre-screen for fines removal
 Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

860mm (34") x 720mm (28.5") Crusher Inlet
 830mm (33") Wide x 860mm (34") diameter rotor
 2 High / 2 Low configuration as standard
 Hydraulic adjust and hydraulic overload protection as standard

SCREEN

2.44m x 1.2m (8' x 4') single deck mesh
 Side tensioned
 Screen can be lowered to horizontal to ease mesh change and maintenance

POWERUNIT

Stage IIIA Constant Speed: John Deere 6068 194 kw (260hp)
 Tier 4 Final: Volvo D8 210kW (281Hp)
 Stage V: Volvo D8 210kW (281Hp)
 Direct Drive to Crusher via clutch and V Belts

OUTPUT POTENTIAL

Up to 250tph / 275 US tph

CONVEYORS

900mm (36") wide product conveyor
 500mm (20") Transfer Conveyor
 500mm (20") Oversize Conveyor with Recirc & Stockpile
 1000mm (48") Fines Conveyor with 2.5m (8'2") discharge

GENERAL

Afterscreen system is quick to detach
 Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	13.3m (43' 7")	2.5m (8' 3")	3m (9' 10")

Weight (with Magnet) Tier 3: 29,100kg (64,155lbs)
 Tier 4F: 29,300kg (64,595lbs)



CRUSHING RANGE

COBRA 290



HOPPER / FEEDER

3.3m³ (4.3yd³) Hopper Capacity
 Integrated pre-screen for fines removal
 Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

1030mm (41") x 790mm (31") Crusher Inlet
 1000mm (40") Wide x 1034mm (41.5") diameter rotor
 2 High / 2 Low configuration as standard
 Max OSS - 150mm (6") upper; 75mm (3") lower
 Min CSS - 50mm (2") upper; 20mm (0.75") lower
 Hydraulic adjust and hydraulic overload protection as standard
 Hinged crusher inlet lid as standard

POWERUNIT

Tier 3 Equivalent: Volvo D8 235 kW (315hp)
 Tier 4 Final: Volvo D8 235kW (315Hp)
 Stage V: Volvo D8 235kW (315Hp)
 Direct Drive to Crusher via Clutch and V Belts

OUTPUT POTENTIAL

Up to 290tph / 320 US tph

CONVEYORS

1000mm (40") wide product conveyor
 Product conveyor discharge height: 3.42m (11' 3")

GENERAL

Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.92m (32' 6")	2.55m (8' 4")	3.16m (10' 4")

Weight (with Magnet) Tier 3: 28,700Kgs (63,273lbs)
 Tier 4F: 28,700Kgs (63,273lbs)

CRUSHING RANGE

COBRA 290R

HOPPER / FEEDER

3.3m³ (4.3yd³) Hopper capacity
 Integrated pre-screen for fines removal
 Feeder speed auto-regulates depending on crusher load.

IMPACT CRUSHER

1030mm (41") x 790mm (31") crusher inlet
 1000mm (40") x 1034mm (41.5")
 Max OSS - 150mm (6") upper, 75mm (3") lower
 Min CSS - 50mm (2") upper, 20mm (3/4") lower
 2 high / 2 low configuration as standard
 Hydraulic adjust and hydraulic overload as standard

SCREEN

2.74m x 1.5m (9'x5') single deck screen
 Wide range of screen media
 Side tensioned
 Screen can be lowered to horizontal to ease mesh change and maintenance

POWERUNIT

Tier 3 Equivalent: Volvo D8 235 kW (315hp)
 Tier 4 Final: Volvo D8 235kW (315Hp)
 Stage V: Volvo D8 235kW (315Hp)
 Direct Drive to Crusher via clutch and V belts

OUTPUT POTENTIAL

Up to 290tph / 320 US tph

CONVEYORS

1000mm (40") Wide product conveyor
 500mm (20") wide side conveyor (option)
 Side Conveyor (option) discharge height 2.48m (8'2")
 500mm (20") transfer conveyor
 500mm (20") Oversize conveyor with Recirc & Stockpile.
 1200mm (47") Fines Conveyor with 3m (9'10") discharge

GENERAL

Intuitive 'Push button' control system
 Afterscreen system is quick to detach

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	14.76m (48'5")	2.9m (9'6")	3.16m (10'4")

Weight (with Magnet) Tier 3: 34,200kg (75,398lbs)
 Tier 4F: 34,200kg (75,398lbs)



SCREENERS



SCREENING RANGE

COLT 600



FEEDER

3m³ (3.9yd³) Hopper capacity
 1m (40") Wide
 Variable speed
 Maximum feed size: 300mm (12")

SCREEN

2.34m x 1.17m (8' x 4') Double deck screen
 Wide range of screen media
 Top deck - Bofor Deck, Fingers, Punch Plate & Mesh;
 Bottom Deck - Mesh & Fingers

POWERUNIT

Tier 3: Deutz D2011 L04I - 36.4kW (48.8 Hp) @ 2300 RPM.
 Tier 4F / Stage IV: Deutz TD2.9L4 - 42kW (56 Hp) @ 1900 RPM

OUTPUT POTENTIAL

Up to 280 tph / 308 US tph

CONVEYORS

650mm (26") Wide fines conveyor with 2.9m (9'6") discharge
 650mm (26") Wide midgrade conveyor with 2.8m (9'2") discharge
 1000mm (40") Wide oversize conveyor with 2.7m (8'10") discharge
 Variable speed on midgrade and oversize as standard
 Ability to convert to 2 way split

TRANSPORT

Containerisable
 Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	10.98m (36')	2.25m (7'5")	2.55m (8'4")

Weight (standard machine): 12,000Kgs (26,455lbs)

SCREENING RANGE

COLT 800

FEEDER

2.9m³ (3.8yd³) Standard hopper capacity
 4.7m³ (6.1yd³) Extended hopper capacity (Option)
 1050mm (42") wide
 Variable speed

SCREEN

2.77m x 1.22m (9' x 4') Double deck screen
 Wide range of screen media
 Top Deck - Bofor Deck, Fingers, Punch Plate & Mesh;
 Bottom Deck - Mesh & Fingers

POWERUNIT

Tier 3: Deutz TD2011 L04I - 49.4kW (66Hp) @ 2300rpm
 Tier 4F / Stage IV: Cat C3.4 - 55kW (74Hp) @ 2300rpm
 Simple to operate



OUTPUT POTENTIAL

Up to 280 tph / 308 US tph

CONVEYORS

1050mm (42") Wide collection conveyor with SCS scraper
 650mm (26") Wide fines conveyor with 3.82m (127") discharge
 650mm (26") Wide midgrade conveyor with 3.64m (11'11") discharge
 1050mm (42") Wide oversize conveyor with 3.03m (9'11") discharge
 Hydraulic combined slide out and fold mechanism
 Variable speed on fines, midgrade and oversize as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.22m (30'3")	2.5m (8'2")	3.09m (10'1")

Weight (standard machine): 16,700Kgs (3,6817lbs)



SCREENING RANGE

COLT 1000



HOPPER / FEEDER

5m³ (6.5yd³) Hopper Capacity
 1100mm (44") wide
 Variable speed

SCREEN

4.1m (13'6") x 1.22m (4') Double deck screen
 Variable screen angle
 Wide range of screen media
 Top Deck - Bofor Deck, Fingers, Punch Plate, 3D Punch Plate & Mesh
 Bottom Deck - Mesh & Fingers

POWERUNIT

Tier 4 Final/ Stage IIIB: CAT C3.4 engine (55kW / 74hp @ 2300rpm)
 Simple to operate

OUTPUT POTENTIAL

Up to 360 tph / 396 US tph

CONVEYORS

1000mm (40") Wide collection conveyor with SCS scraper
 800mm (31") Wide fines conveyor with 3.9m (12'8") discharge
 650mm (26") Wide midgrade conveyor with 3.7m (12'2") discharge
 1050mm (41") Wide oversize conveyor with 3.2m (10'4") discharge
 Configurable layout and ability to convert to 2 way split
 Variable speed on fines, midgrade and oversize as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.0m (35' 11")	2.50m (8' 2")	3.10m (10' 4")

Weight (standard machine) Tier 4F: 20,750Kgs (45,745lbs)

SCREENING RANGE

HARRIER 220



SCREEN

2.1m (6'9") x 1.1m (3'6") Double deck screen
600mm x 1.1m (2' x 3'6") Feed in area
End tensioned as standard

POWERUNIT

Isuzu engine (21kW / 28.5hp)
Simple to operate

OUTPUT POTENTIAL

Up to 80tph / 90 US tph



CONVEYORS

1000mm (40") Wide collection conveyor with 1.93m (6' 4") discharge
500mm (20") Wide midgrade conveyor with 1.18m (3'10") discharge

TRANSPORT

Containerisable
Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	4.36m (14' 4")	1.8m (5' 11")	2.23m (7' 4")

Weight: 3,300Kgs (7,275lbs)

SCREENING RANGE

HARRIER 750

SCREEN

4.5m x 2.6m (14'8" x 8'7") Double deck grid
Split level cassettes as standard
Standard grid opening - 150mm (6"); 100mm (4") is optional
Standard bottom deck mesh - 60mm (2.4")

POWERUNIT

Tier 3: Deutz D914 53kW (71Hp) @2300rpm
Tier 4 / Stage IV: Cat C3.4 - 55kW (74Hp) @ 1800rpm

OUTPUT POTENTIAL

Up to 600tph / 660 US tph

CONVEYORS

1200mm (48") Wide product conveyor with discharge height of 3.4m (11'2")
Hydraulically folding for transport
Twin drive as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.43m (31')	2.82m (9'3")	3.2m (10'6")

Weight (standard machine): 19,000Kgs (41,890lbs)



CONVEYORS



CONVEYOR RANGE

TC65

CONVEYOR

Conveyor Length: 20m (65' 7")
Belt Width: 1050mm (42")
Discharge Height @ 24°: 8.7m (28' 6")
Max Discharge Height @ 28°: 10m (32' 10")
Capacity: Up to 500tph (551 US tph)
Hydraulic Folding Head Section
Belt Type: Plain - 3 Ply
Feedboot with removable 6mm steel wear liners
Variable speed control

POWERUNIT

Diesel Hydraulic
Tier 3 / Stage III3A: Deutz D2011 L04I 36.4 kW (49hp)
Tier 4 Final: Deutz TD 2.9 L4 41kW (56hp)

CURRENT OPTIONS

Various options available, contact us for further information

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.3m (37')	2.25m (7'5")	2.53m (8'4")

Weight: 12,750kg (28,109lbs)
Containerised shipping 40' x 9'6"
High Cube Container



CONVEYOR RANGE

TC80

CONVEYOR

Conveyor Length: 23.5m (77')
 Belt Width: 1050mm (41")
 Discharge Height @ 24°: 9.95m (32' 8")
 Max Discharge Height @ 25°: 10.1m (32' 2")
 Capacity: Up to 500 tph (551 US tph)
 Hydraulic Folding Head Section
 Belt Type: Plain - 3 Ply
 Feedboot with removable 6mm steel wear liners
 Variable speed control

POWERUNIT

Diesel Hydraulic
 Tier 3 / Stage III3A: Deutz D2011 L04I 36.4 kW (45hp)
 Tier 4 Final: Deutz TD 2.9 L04 45kW (60hp)

CURRENT OPTIONS

Various options available, contact us for further information

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.88m (38'11")	2.26m (7'5")	2.54m (8'4")

Weight: 16,000kg (35,274lbs)
 Containerised shipping 40' x 9'6"
 High Cube Container



CONVEYOR RANGE

TC100

CONVEYOR

Conveyor Length: 30m (98' 6")
 Belt Width: 1050mm (41")
 Discharge Height @ 18°: 10.5m (34' 5")
 Max Discharge Height @ 25°: 13.1m (42' 11")
 Capacity: Up to 600 tph (661 US tph)
 Hydraulic Folding Head Section
 Belt Type: Plain - 3 Ply
 Feedboot with removable 6mm steel wear liners
 Variable speed control

POWERUNIT

Diesel Hydraulic
 Tier 3 / Stage 3A: CAT 4.4 - 4 cylinder diesel engine developing 83kW (111hp)
 Tier 4 Final / Stage IV: Caterpillar C4.4 - 4 cylinder diesel engine developing 82kW (110hp)

CURRENT OPTIONS

Various options available, contact us for further information

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	19.5m (63' 11")	2.84m (9'4")	3m (9' 9")

Weight (Est): 24,000kg (52,910lbs)
 Containerised shipping 40' x 9'6"
 High Cube Container



CONVEYOR RANGE

TC75R

CONVEYOR

Conveyor length 22.9m (75' 2")
 Belt width 1050mm (41")
 Discharge height 9m (29' 6") @ 18°
 Max. discharge height 10.9m (35' 9") @ 23°
 Production capacity Up to 600 tph (661 US tph)

POWERUNIT

Diesel Hydraulic
 Stage 3A: CAT 4.4 - 4 cylinder diesel engine developing 83kW (111HP)
 Tier 4F / Stage IV - CAT C4.4 - 4 cylinder diesel engine developing 82kW (110HP)
 Stage V Deutz TD2.9 L4 45kW complete with radiator

CHASSIS

Tracks: 2.9m centres x 400mm shoe
 2 Speed Track Motor
 Lower Speed: 0.9Km/h
 Higher Speed: 1.6Km/h

CURRENT OPTIONS

Various options available, contact us for further information

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	15.6m (51' 3")	2.25m (7' 5")	3m (9' 9")

Weight (Est.): 19,500kg (42,990lbs)
 Containerised shipping 40' x 9'6"
 High Cube Container



CONVEYOR RANGE

HLF75 HIGH LEVEL FEEDER

CONVEYOR

Conveyor length: 22.6m (74' 2")
 Belt width: 1200mm (3' 11")
 Belt spec: 3 ply, 4 + 2 plain belt
 Conveyor drive: variable speed, 110m/min
 Optimum working angle: 18°
 Optimum discharge height: 8.0m (26' 3")
 Stockpile capacity at optimum working angle based on 37° angle of repose: 944m³
 Max. working angle: 24°
 Max. discharge height: 9.8m (26' 3")
 Capacity: up to 600 tph (661 US tph)

POWERUNIT

Stage 3A CAT 4.4 - 4 cylinder diesel engine developing 83kw (111hp)
 Tier 4F / Stage IV - Caterpillar C4.4 - 4 cylinder diesel engine developing 82kW (110 Hp)

FEEDER

Capacity: 8m³ (10.5yd³)
 Feed height: 2545mm (8' 2")
 Feed in width: 3800mm (12' 6")
 Drive: hydraulic variable speed drive via high torque gearbox
 Wearplate Hopper
 Hydraulic adjustable jacking legs

CURRENT OPTIONS

Various options available, contact us for further information

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)
 Containerisation, packed into 2 x 40ft high cube containers

	LENGTH	WIDTH	HEIGHT
Track Unit	19.5m (64')	3.12m (10'2")	2.75m (9')

Weight: 25,000kg (55,116lbs)



CONVEYOR RANGE

LLF75 LOW LEVEL FEEDER

CONVEYOR

Conveyor
 Conveyor length: 22.6m (74' 2")
 Belt width: 1200mm (3' 11")
 Belt spec: 3 ply, 4 + 2 plain belt
 Conveyor drive: variable speed, 110m/min
 Optimum working angle: 18°
 Optimum discharge height: 8.0m (26' 3")
 Stockpile capacity at optimum working angle based on 37° angle of repose: 994m³
 Max. working angle: 24°
 Max. discharge height: 9.8m (32' 2")
 Capacity: up to 600 tph (661 US tph)

POWERUNIT

Stage 3A CAT 4.4 - 4 cylinder diesel engine developing 83kw (111hp)
 Tier 4F / Stage IV - Caterpillar C4.4 - 4 cylinder diesel engine developing 82kW (110 Hp)

FEEDER

Capacity: 7m³ (9.2yds³)
 Feed height: 1900mm (6' 2")
 Feed in width: 3500mm (11' 6")
 Twin drive hydraulic variable speed via high torque gearbox
 Wearplate Hopper (No liners)
 Hydraulic folding hopper flares

CURRENT OPTIONS

Various options available, contact us for further information

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)
 Containerisation, packed into 2 x 40ft high cube containers

	LENGTH	WIDTH	HEIGHT
Track Unit	19.6m (64'4")	3m (10')	2.75m (9')

Weight: 24,000kg (52,910lbs)



FINANCIAL SERVICES

ADDING VALUE TO YOUR BUSINESS



Terex Financial Services (TFS) is fully integrated into the fabric of the Terex Business

We are committed to working with our dealers and customers in developing and adding true value to their business, and assisting in the acquisition and funding of their Terex equipment.

TFS offer global solutions and through a team of dedicated people who understand the needs of our dealers and customers we can direct you to the correct financial solution for your business.

We have developed a Turnkey Funding solution to assist our dealer partners, this offer is designed to maximize a dealers potential to develop their Terex Business.

- Terex Self-funding Capability
- Improved Working Capital Management
- Demonstration Programs
- Rental Purchase Schemes
- Stock Programs

Programs are tailored by region through a panel of funders.

TFS offers a comprehensive suite of finance and leasing facilities for the end user.

The concept of adding value to your business is critical to us and this is why the TFS Team can assist you in developing the right solution for you.

These facilities can be developed and tailored to suit the individual needs of each customer.

We offer a wide range of facilities tailored by region:

- USA
- Canada
- EMEA
- JAPIC region

The range of facilities and services available are as follows;

- Leasing Solutions
- Operating lease Solutions
- Fair Market Value lease solutions
- Loans/Hire Purchase facilities
- Used Equipment Financing
- Asset Management

COMPACT WITH IMPACT



CRUSHING RANGE



SCREENING RANGE



CONVEYOR RANGE



The material in this document is for information only and is subject to change without notice. EvoQuip assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein.

Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples. These results will vary depending on application. Photographs are for illustrative purposes only; some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras.

Published and Printed in January 2019. All machines are CE Approved.

© Terex Corporation 2019

200 Coalisland Road,
Dungannon, Co. Tyrone, BT714DR

Tel: +442887718500 **Email:** evoquip@terex.com



terex.com/EvoQuip