

CRC1150 PORTABLE CONE PLANT



Unit shown with optional electrical switchgear panel, power cables, and hydraulic run-on jacks.

STANDARD FEATURES


- ▶ Terex® TC1150 cone crusher: standard mantle and medium coarse concave poured, oil lubrication tank with air blast cooler with piping, standard crusher tool kit and System 2 hydraulic controls
- ▶ 300 hp (225 kW) 1800 rpm crusher motor and drive mounted with crusher on rubber isolated frame
- ▶ Oversize quick-release cone feed hopper with gated overflow chute
- ▶ “Straight-line” undercrusher conveyor 42"x34'6" (1067x10515mm) with 15 hp (11 kW) electric motor and shaft mount gearbox
- ▶ 3-ply conveyor belt with vulcanized belt splice and primary style belt wiper
- ▶ Metal detector for off-plant feed conveyor (interlocked with off-plant feed conveyor if plant is outfitted with the optional switchgear panel); lockable stowage box for metal detector
- ▶ Service platforms around crusher, elevated observation platform, guard rails and access ladders
- ▶ Easy maintenance features
 - Conveniently located grease banks
 - Ground access cone lubrication module
- ▶ Emergency stop stations on both sides of frame
- ▶ Tandem axle spring suspension
- ▶ Eight 295/75 R22.5 tires
- ▶ Side-mounted lockable storage box

OPTIONAL EQUIPMENT


- ▶ Removable electrical switchgear panel with crusher soft start and door-mounted controls, two 25 hp (20 kW) off-plant conveyor controls
- ▶ Manual crank-style landing jacks
- ▶ Hydraulic leveling or run-on jacks (gas, 12V or 24V powered)
- ▶ Power cables and quick disconnects
- ▶ Oversize 315/80 R22.5 tires

SPECIFICATIONS

Terex® Minerals Processing Systems Cedarapids® CRC1150 Portable Cone Plant



Operating Position



Transport Position - Unit shown with the following options: electrical switchgear panel and hydraulic run-on jacks.

Total Weight: 66100 lbs (29990 kg); Kingpin: 30900 lbs (14020 kg); Rear Axle: 35200 lbs (15970 kg); Weights include the options shown.

www.terexmps.com

Effective Date: March 2016. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or failure to act responsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. Terex, the Terex Crown design, Works For You, and Cedarapids are trademarks of Terex Corporation or its subsidiaries. All rights are reserved. © 2016 Terex Minerals Processing Systems.

Terex® Minerals Processing Systems, 909 17th Street NE, Cedar Rapids, IA 52402 USA
Tel +1 319 363 3511 ▪ Fax +1 319 399 4871 ▪ Email MPSsales@terex.com ▪ www.terexmps.com

Form 26736 (3/16)



WORKS FOR YOU.™